



2-INCH PRESSURE CONTROL FITTING

**MATERIAL LIST**

| QTY | DESCRIPTION   | STOCK NO.                  | QTY | DESCRIPTION | STOCK NO. |
|-----|---|----------------------------|-----|-------------|-----------|
| 1   | EXISTING STEEL GAS MAIN   |                            |     |             |           |
| 2   | SHORTSTOP WELDING FITTING<br>2" SHORTSTOP FITTING<br>4" SHORTSTOP FITTING<br>6" SHORTSTOP FITTING | 206285<br>205096<br>201013 |     |             |           |
| 3   | FITTING SIZE PANCAKE VALVE<br>SUPPLIED BY PRESSURE CONTROL.                                       |                            |     |             |           |

**GENERAL NOTES**

- 1 MAXIMUM 60 PSI WORKING PRESSURE.
- 2 TAP IS MADE WITH THE USE OF A T.D. WILLIAMSON DRILLING MACHINE. COMPLETION OF THE STOP IS DONE WITH WILLIAMSON SHORT STOP PLUGGING MACHINE. CHIP SWEEP MUST BE USED TO CLEAN OUT METAL SHAVINGS PRIOR TO INSERTING RUBBER STOPPER.

**CONSTRUCTION STANDARD  
CITY UTILITIES  
OF SPRINGFIELD, MISSOURI**

PRESSURE CONTROL  
FITTING  
INSTALLATION